



TEKNOKOTE™ SIEGER SL 59

Aerosol Penetrating Fluid

Description

TEKNOKOTE™ Sieger SL 59 Penetrating Oil is optimized to afford the best rust busting characteristics while keeping your metals, plastics and paint safe. It has high hydrophobicity, which repels water, and low viscosity, which reduces friction and wear.

Keterangan

TEKNOKOTE™ Sieger SL 59 Penetrating Oil dioptimalkan untuk menghasilkan karakteristik penghilang karat terbaik sekaligus menjaga keamanan logam, plastik, dan cat Anda. Ia memiliki hidrofobisitas tinggi, yang menolak air, dan viskositas rendah, yang mengurangi gesekan dan keausan.

Technical Data

Appearance	: Amber
Odor	: Hydrocarbon
Specific Gravity @15°C	: 0.80
Viscosity @40°C	: 3.0 – 6.0
Flash Point, COC	: > 65

Benefit

- Excellent penetrating ability while still remaining plastic and paint safe.
- CFC Free, Chlorinated Solvent Free will not harm the ozone layer.
- Silicone free.
- Economical.

Manfaat

- Kemampuan penetrasi yang sangat baik namun tetap aman dari plastik dan cat.
- Bebas CFC, Bebas Pelarut Terklorinasi tidak akan merusak lapisan ozon.
- Bebas silikon.
- Ekonomis.

Application

TEKNOKOTE™ Sieger SL 59 for lubricating, penetrating, and cleaning metal parts like nuts, bolts, locks, hinges, screws, clamps, shaft, pulleys, scales, and more. As well, it affords excellent corrosion resistance.

Cara Pemakaian

TEKNOKOTE™ Sieger SL 59 untuk melumasi, menembus, dan membersihkan bagian logam seperti mur, baut, kunci, engsel, sekrup, klem, poros, katrol, timbangan, dan lainnya. Selain itu, ia memberikan ketahanan korosi yang sangat baik.

Packaging

400 mL/Spray Can

Kemasan

400 mL/Spray Can

Disposal Information

Dispose of TEKNOKOTE™ Sieger SL 59 per local, state and regional regulations. Refer to your Material Safety Data Sheet for additional disposal information.

Informasi Pembuangan

Buang TEKNOKOTE™ Sieger SL 59 sesuai peraturan lokal, negara bagian, dan regional. Lihat Lembar Data Keamanan Material Anda untuk informasi pembuangan tambahan.

Storage

Store in cool dry place. Avoid direct sunlight.

Penyimpanan

Simpan di tempat kering yang sejuk. Hindari sinar matahari langsung.

This information is based on our current level of knowledge. It is given in good faith but it is not intended to guarantee any particular properties. The users must satisfy themselves that there are no circumstances requiring additional information or precaution or the verification of details given here in.



VISILUBE
TEKNO
REKATAMA

TDS

www.visilube.com

address:

Ruko Bizhub Blok RE
No.18, Gunung Sindur,
Bogor-Jawa Barat
16340

phone:

(021) 7568 4035

mail:

info@visilube.com



VISILUBE
TEKNO
REKATAMA

Shelf Life

The shelf life for this product is 2 years when it is stored in its original, sealed container at room temperature. However, the product should be inspected after 2 years from the date of manufacture prior to customer use.

Others

If you have any complaints, feedbacks, suggestions, and questions about this product and the data in this document please send it to info@visilube.com

Umur Simpan

Umur simpan produk ini adalah 2 tahun bila disimpan dalam wadah aslinya yang tertutup rapat pada suhu kamar. Namun, produk tersebut harus diperiksa setelah 2 tahun sejak tanggal pembuatan sebelum digunakan oleh pelanggan.

Lainnya

Jika Anda mempunyai keluhan, masukan, saran, dan pertanyaan mengenai produk ini dan data dalam dokumen ini silakan kirimkan ke info@visilube.com

TDS

www.visilube.com

address:

Ruko Bizhub Blok RE
No.18, Gunung Sindur,
Bogor-Jawa Barat
16340

phone:

(021) 7568 4035

mail:

info@visilube.com

This information is based on our current level of knowledge. It is given in good faith but it is not intended to guarantee any particular properties. The users must satisfy themselves that there are no circumstances requiring additional information or precaution or the verification of details given here in.