

VISILAYER 110

Rust Preventive Oil

Description

VISILAYER 110 is an economical water displacing rust preventive. It is a dark brown fluid and semi-oily light colored film. Prevents rust and corrosion on metal surface for long periods.

It is able to provide protection under condition of outdoor exposure.

Health & Safety

VISILAYER 110 is unlikely to present any significant health or safety hazard when properly used in the recommended application. For further detail, please refer to Material Safety Data Sheet.

| Technical Data | | |
|--------------------------|--------------|--|
| Appearance | Brown Liquid | |
| Odor | Hydrocarbon | |
| Specific Gravity | 0.85 g/L | |
| рН | 8 – 9 | |
| Flash Point | > 70 | |
| Viscosity (@ 25₀C - cps) | 3.9 | |
| Solubility in Water | insoluble | |

Benefit

- High performance water displacing.
- Excellent penetrating properties.
- Provide outdoor protection.

Application

VISILAYER 110 is a general rust preventive oil which applied to prevent metal parts from corrosion in the periode of 1 - 3 months, indoor condition.

Applied VISILAYER 110 in metal parts, after processing. The application can be brushed, dyed or sprayed, directly to the metal parts. Dispose of VISILAYER 110 per local, state and regional regulations. Refer to your MATERIAL SAFETY DATA SHEET for additional disposal information.

Storage

Store in cool dry place. Avoid direct sunlight.

Shelf Life

The shelf life for this product is 2 years when it is stored in its original, sealed container at room temperature. However, the product should be inspected after 2 years from the date of manufacture prior to customer use.

Packaging

20 liters/pail 200 liters/drum

Others

If you have any complaints, feedbacks, suggestions, and questions about this product and the data in this document please send it to <u>info@visilube.com</u>

PT Visilube Tekno Rekatama

JI. Wijaya Kusuma Blok F49 CInere Jawa Barat 16513 Indonesia