



VISILUBE TEKNO REKATAMA

PRODUCT DATA SHEET

RUSTYKLIN 222

Rust Remover

Description

RUSTYKLIN 222 is a very effective acid rust remover. It even removes deep rust on all types of mild steel and iron. Rust Clean 501 is an organic environmentally safe industrial grade, rust and oxidation remover that dissolves even the heaviest corrosion from metals and is simultaneously harmless to humans and the environment.

Health & Safety

RUSTYKLIN 222 is unlikely to present any significant health or safety hazard when properly used in the recommended application. For further detail, please refer to Material Safety Data Sheet.

Technical Data

Appearance	Opaque Yellowish
Odor	Mild
Specific Gravity	0.98 – 1.20 Kg/liter
pH	<2
Flash Point	None
Solubility in Water	Soluble

Benefit

- Fast acting
- Ferrous and non-ferrous metals
- Organic compounds and biodegradable
- Non-polluting for easy disposal
- Non-flammable and non-toxic
- Aqueous & operator friendly

Disposal Information

Dispose of RUSTYKLIN 222 per local, state and regional regulations. Refer to your MATERIAL SAFETY DATA SHEET for additional disposal information.

Application

- Highly recommended to degrease parts before using RUSTYKLIN 222. By degreasing the parts, the de-rusting process is accelerated.
- Immerse parts in the solution at room temperature.
- Let react for a minimum of 30 minutes and a maximum of 48 hrs.
- Reaction time varies depending on the severity of the rust, presence of surface contaminants and solution temperature.
- The rust removal rate will be doubled by increasing the liquid temperature between 40 & 60° C (120 & 140° F)
- The rust removal rate will also be accelerated two to three times when used in an ultrasonic bath.

Storage

Store in cool dry place. Avoid direct sunlight.

Shelf Life

The shelf life for this product is 2 years when it is stored in its original, sealed container at room temperature. However, the product should be inspected after 2 years from the date of manufacture prior to customer use.

Packaging

25 liters/pail
200 liters/drum

Others

If you have any complaints, feedbacks, suggestions, and questions about this product and the data in this document please send it to info@visilube.com

PT Visilube Tekno Rekatama

Jl. Wijaya Kusuma Blok F49
Clnere Jawa Barat 16513 Indonesia