



VISILUBE TEKNO REKATAMA

TEKNOKOTE™

FIRECOMBAT 06

AFFF 6%

PRODUCT DATA SHEET

DESCRIPTION

TEKNOKOTE™ FIRECOMBAT 06 is a water-based foaming agent specially formulated as fire fighting foam concentrate. TEKNOKOTE™ FIRECOMBAT 06 is intended for use at a proportioning rate of 6% (6 parts AFFF concentrate to 94 parts water) Effective to hydrocarbon fuels such as gasoline, kerosene, diesel, etc.

HEALTH & SAFETY

FIRECOMBAT 06 is unlikely to present any significant health or safety hazard when properly used in the recommended application. For further detail, please refer to Material Safety Data Sheet.

Technical Data

| | |
|-------------------------|---------------------------|
| Appearance | Clear light yellow liquid |
| pH | 7.0-8.5 |
| Specific Gravity @ 15°C | 1.0±0.2 |
| Solubility in water | Soluble |

BENEFIT

High quality foam blanket It is a foaming agent which produces a very high quality foam blanket that floats on the fuel surface.

• Quick extinguisher

Foams of TEKNOKOTE™ FIRECOMBAT 06 will extinguish hydrocarbon fuel fires (gasoline, kerosene, diesel, etc) and cover the fuel surface quickly.

• Smooth and stable foam

Foams prepared using TEKNOKOTE™ FIRECOMBAT 06 show a fine, even cell structure and stable.

• Water based, PFAS & Fluorine Free

Water based. Safe and easy to use. Non toxic. Doesn't contain per/polyfluoroalkyl substances.

APPLICATION

• TEKNOKOTE™ FIRECOMBAT 06 is intended for use at 6% proportioned solution in both fresh and salt water.

• TEKNOKOTE™ FIRECOMBAT 06 is ideal fire fighting foam for hydrocarbon fuels as gasoline, kerosene, diesel etc.

• TEKNOKOTE™ FIRECOMBAT 06 is not recommended for use on fuels having considerable water solubility like alcohols, ketones etc.

DISPOSAL INFORMATION

Dispose of FIRECOMBAT 06 per local, state and regional regulations. Refer to your MATERIAL SAFETY DATA SHEET for additional disposal information.

SHELF LIFE

The shelf life for this product is 2 years when it is stored in its original, sealed container at room temperature. However, the product should be inspected after 2 years from the date of manufacture prior to customer use.

PACKAGING

25 liters/pail
200 liters/drum

STORAGE

Store in cool dry place. Avoid direct sunlight.

OTHERS

If you have any complaints, feedbacks, suggestions, and questions about this product and the data in this document please send it to info@visilube.com

PT VISILUBE TEKNO REKATAMA

Ruko Bizhub Blok RE no.18 Jl. Raya Serpong Puspitek No. 99, Kel Pabuaran, Kec Gunung Sindur Kab. Bogor Jawa Barat - Indonesia, Phone: (021) 75684035 E-mail: info@visilube.com